

Linear power adapter	Desktop type
Model:	YL15E
Rated Power:	15W
Input:	100-120 VAC 60Hz or 220-240VAC 50Hz
Output Voltage:	9-36VAC
Output Current:	0.4-1.2A
Input current:	0.25A max or 0.125A max.
Inrush Current:	65 Amps max. at 230VAC/50Hz, full load
Leakage Current:	0.25mA Max. at 264VAC input
No Load Power Consumption :	< 1.5W
Protections:	Short Circuit /Over Current /Over Voltage
Short Circuit Protection (SCP):	Protection to Zero Voltage
Over Voltage Protection (OVP):	$\leq V_{out} * 150\%$
Over Current Protection (OCP):	110%-180%
Working TEMP.:	-20°C-50°C
Working Humidity:	5%-90% RH non-condensing
Storage TEMP., Humidity and altitude:	40°C ~+70°C ambient temperature and a 5% to 95% relative humidity range throughout an altitude range of -60 meters to +5000 meters AMSL.
Input Plug:	EU,US,UK,AU etc. type according to customer's choice
Certificates and approvals:	GS,CE,EMC,SAA,FCC,CB,PSE,CCC,RoHS,REACH
EMI EMISSION:	Radiation Test&Conduction Test: EN 55022/FCC Part 15 Harmonic Test : EN 61000-3-2 Flicker Test : EN 61000-3-3
EMS IMMUNITY:	ESD Test:EN 61000-4-2 RS Test:EN 61000-4-3 EFT Test:EN 61000-4-4 Surge Test:EN 61000-4-5 CS Test:EN 61000-4-6 DIP Test:EN 61000-4-11
MTBF:	100000 hours minimum at full load at 25 C ambient
Life:	3-5 years alternative
Dimension:	81*55*47mm
Weight:	490g
Packing:	20PCS/CTN,53.5*26*15.5cm