



### RM-F series

### RM-K series

### RM-U series

Push-Pull Self-Latching system	Push-Pull Self-Latching system	Push-Pull Self-Latching system
Shell size:0F,1F,AF,2F,3F	Shell size:0K,1K,2K,3K	Shell size:0U,1U
Multipole contacts:2-19 contacts	Multipole contacts:2-32 contacts	Multipole contacts:2-19 contacts
Natural and Black Chrome Plated Brass	Natural and Black Chrome Plated Brass	Natural and Black Chrome Plated Brass
OEM / ODM	OEM / ODM	OEM / ODM
CE,SGS,ROHS,ISO9001:2015	CE,SGS,ROHS,ISO9001:2015	CE,SGS,ROHS,ISO9001:2015
Temperature range:-55°C~250°C	Temperature range:-55°C~250°C	Temperature range:-55°C~250°C
Various contact types:Straight solder, Print and Elbow print 90°	Various contact types:Straight solder, Print and Elbow print 90°	Various contact types:Straight solder, Print and Elbow print 90°
360°screening for full EMC shielding	360°screening for full EMC shielding	360°screening for full EMC shielding
<b>IP68</b>	<b>IP68</b>	<b>IP68</b>
Cable diameter:1-10mm	Cable diameter:1-11mm	Cable diameter:1-10mm



### RM-V series

### RM-T series

### RM-E series

Screw Locking System	Push-Pull Self-Latching system	Push-Pull Self-Latching system
Shell size:0V,1V,2V	Shell size:0T	Shell size:1E
Multipole contacts:2-26 contacts	Multipole contacts:2-9contacts	Multipole contacts:1-6 contacts
Natural and Black Chrome Plated Brass	Natural and Black Chrome Plated Brass	Natural and Black Chrome Plated Brass
OEM / ODM	OEM / ODM	OEM / ODM
CE,SGS,ROHS,ISO9001:2015	CE,SGS,ROHS,ISO9001:2015	CE,SGS,ROHS,ISO9001:2015
Temperature range:-55°C~250°C	Temperature range:-55°C~250°C	Temperature range:-55°C~250°C
Various contact types:Straight solder, Print and Elbow print 90°	Various contact types:Straight solder, Print and Elbow print 90°	Various contact types:Straight solder and Print and Elbow print 90°
360°screening for full EMC shielding	360°screening for full EMC shielding	360°screening for full EMC shielding
<b>IP68</b>	<b>IP68</b>	<b>IP68</b>
Cable diameter:1-8mm	Cable diameter:1-5mm	Cable diameter:1-7mm